

# ALL ROUND™ STRAPPING

Issued: 5-May-11  
Effective: 5-May-11



1/2" - 22GA | 3/4" - 24GA | 3/4" - 20GA

- 1/2" straps have 3/16" bolt holes
- 3/4" straps have large holes for 1/4" bolts and small holes for screw or nails.

THE SMOOTH WAVY EDGES MAKE IT EASIER TO BEND. UNIFORM STRENGTH - NO WEAKNESS AT THE HOLES. NO "RAZOR WIRE" SHARP EDGES

PART NO.	SIZE	GAUGE	LOAD* MAX LBS	FEET /COIL	LIST/COIL CDN\$	COILS /MASTER
<b>STEEL</b>						
9015	1/2"	22 GA	110	10	2.31	40
<b>9010</b>	<b>1/2"</b>	<b>22 GA</b>	<b>110</b>	<b>25</b>	<b>3.15</b>	<b>20</b>
9021	3/4"	24 GA	130	10	2.54	40
<b>9020</b>	<b>3/4"</b>	<b>24 GA</b>	<b>130</b>	<b>25</b>	<b>3.67</b>	<b>20</b>
9025	3/4"	24 GA	130	100	13.72	5
9030	3/4"	20 GA	210	25	6.67	20
9035	3/4"	20 GA	210	100	26.99	5
90100	1/2"	22 GA	110	100	27.77	5
<b>GALVANIZED STEEL</b>						
9049	1/2"	24 GA	95	25	4.98	20
9043	3/4"	24 GA	130	10	2.67	40
<b>9047</b>	<b>3/4"</b>	<b>24 GA</b>	<b>130</b>	<b>25</b>	<b>4.22</b>	<b>20</b>
9048	3/4"	24 GA	130	100	17.04	5
9040	3/4"	20 GA	210	25	5.60	20
9045	3/4"	20 GA	210	100	27.89	5
<b>SOLID COPPER</b>						
9053	1/2"	22 GA	60	10	8.12	40
9050	1/2"	22 GA	60	25	19.68	20
9060	3/4"	24 GA	55	25	24.29	20
9070	3/4"	20 GA	130	25	31.02	20
<b>NYLON COATED (Galvanized Steel)</b>						
<b>Stronger and cheaper than Copper Meets CHMC requirements</b>						
9090	1/2"	24 GA	110	10	6.75	40
9080	1/2"	24 GA	110	25	17.11	20
9085	3/4"	24 GA	130	25	19.10	20

\* INDICATED MAXIMUM LOAD IS APPROXIMATELY 1/3 OF BREAKING LOAD FOR SINGLE STRAPS.